



TECHNICAL DATA

n_1 1400 min⁻¹

	n_2 (min ⁻¹)	Mn_2 (Nm)	Pn_1 (kW)	i
---	-------------------------------	----------------	-------------	-----

BON-IS 20

26.3	120	0.34	53.33
30.5	120	0.40	45.89
34.9	120	0.46	40.10
39.5	120	0.52	35.47
49.1	120	0.64	28.50
59.4	120	0.78	23.56
70.6	120	0.92	19.83
78.4	90	0.77	17.86
95.8	120	1.25	14.62
101	90	1.00	13.80
118	120	1.54	11.90
143	120	1.87	9.81
153	80	1.33	9.17
181	80	1.58	7.72
246	70	1.88	5.69
302	70	2.31	4.63
366	70	2.80	3.82

	n_2 (min ⁻¹)	Mn_2 (Nm)	Pn_1 (kW)	i
---	-------------------------------	----------------	-------------	-----

BON-IS 30

24.1	300	0.79	58.09
28.0	300	0.92	50.02
32.0	300	1.05	43.75
36.1	300	1.18	38.73
40.4	300	1.32	34.62
49.5	300	1.62	28.30
64.3	280	1.96	21.78
81	280	2.47	17.33
93	260	2.64	15.06
113	260	3.21	12.37
136	240	3.57	10.28
177	180	3.47	7.93
222	180	4.36	6.31
255	150	4.18	5.48
311	150	5.09	4.50
374	150	6.12	3.74

BON-IS 25


25.9	200	0.57	54.00
30.1	200	0.66	46.46
34.5	200	0.75	40.60
39.0	200	0.85	35.91
48.5	200	1.06	28.88
58.7	200	1.28	23.85
69.7	200	1.52	20.08
81.9	140	1.25	17.10
94.5	200	2.06	14.81
106	140	1.62	13.21
116	200	2.53	12.05
141	200	3.08	9.93
159	120	2.09	8.78
189	120	2.48	7.39
257	100	2.80	5.45
316	100	3.45	4.43
383	80	3.34	3.66

BON-IS 35



24.1	500	1.31	58.09
28.0	500	1.53	50.02
32.0	500	1.75	43.75
36.1	500	1.97	38.73
40.4	500	2.21	34.62
49.5	500	2.70	28.30
64.3	480	3.37	21.78
81	480	4.23	17.33
93	460	4.66	15.06
113	460	5.68	12.37
136	440	6.54	10.28
177	260	5.01	7.93
222	260	6.29	6.31
255	230	6.41	5.48
311	230	7.80	4.50
374	200	8.17	3.74

Nota:

Pn_1 è una potenza meccanica di ingresso che deve essere ridotta del fattore di riscaldamento al fine di ottenere quello rilevante. Per maggiori informazioni si prega di contattare il nostro Servizio Tecnico



BON HELICAL GEAR BOXES

P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF		
------------------	------------------	------------------	---	----	---	---

P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF		
------------------	------------------	------------------	---	----	---	---

0.12

4 Pole (1400 rpm)	26	42	53.33	2.9	BON 20	B5/B14
	31	36	45.89	3.3		B5/B14
	35	32	40.1	3.8		B5/B14
	39	28	35.47	4.3		B5/B14
	49	22	28.5	5.4		B5/B14
	59	18.5	23.56	6.5		B5/B14
	71	15.6	19.83	7.7		B5/B14
	78	14	17.86	6.4		B5/B14
	96	11.5	14.62	10.4		B5/B14
	101	10.8	13.8	8.3		B5/B14
	118	9.4	11.9	12.8		B5/B14
	143	7.7	9.81	15.6		B5/B14
	153	7.2	9.17	11.1		B5/B14
	181	6.1	7.72	13.2		B5/B14
	246	4.5	5.69	15.7		B5/B14
6 Pole (960 rpm)	302	3.6	4.63	19.2	B5/B14	
	366	3	3.82	23.3	B5/B14	
	16.9	65	53.33	1.8	BON 20	B5/B14
	19.6	56	45.89	2.1		B5/B14
	22	49	40.10	2.4		B5/B14
	25	43	35.47	2.8		B5/B14
	32	35	28.5	3.4		B5/B14
	38	29	23.56	4.2		B5/B14
	45	24	19.83	5		B5/B14
	50	22	17.86	4.1		B5/B14
	62	17.9	14.62	6.7		B5/B14
	65	16.9	13.80	5.3		B5/B14
	76	14.5	11.90	8.2		B5/B14
	92	12	9.81	10		B5/B14
	98	11.2	9.17	7.1		B5/B14
117	9.4	7.72	8.5	B5/B14		
158	7	5.69	10.1	B5/B14		
194	5.7	4.63	12.4	B5/B14		
236	4.7	3.82	15	B5/B14		

6 Pole (960 rpm)	153	10.8	9.17	7.4	BON 20	B5/B14	
	181	9.1	7.72	8.8		B5/B14	
	246	6.7	5.69	10.4		B5/B14	
	302	5.5	4.63	12.8		B5/B14	
	366	4.5	3.82	15.5		B5/B14	
	16.9	98	53.33	1.2		BON 25	B5/B14
	19.6	84	45.89	1.4			B5/B14
	22	74	40.1	1.6			B5/B14
	25	65	35.47	1.8			B5/B14
	32	52	28.5	2.3			B5/B14
	38	43	23.56	2.8			B5/B14
	45	36	19.83	3.3			B5/B14
	50	33	17.86	2.7			B5/B14
	16.7	99	54.00	2			B5/B14
	19.4	85	46.46	2.3			B5/B14
22	74	40.60	2.7	B5/B14			
25	66	35.91	3	B5/B14			
31	53	28.88	3.8	B5/B14			



0.25



4 Pole (1400 rpm)	26	87	53.33	1.4	BON 20	B5/B14
	31	75	45.89	1.6		B5/B14
	35	66	40.1	1.8		B5/B14
	39	58	35.47	2.1		B5/B14
	49	47	28.5	2.6		B5/B14
	59	39	23.56	3.1		B5/B14
	71	32	19.83	3.7		B5/B14
	78	29	17.86	3.1		B5/B14
	96	24	14.62	5		B5/B14
	101	23	13.8	4		B5/B14
	118	19.5	11.9	6.2		B5/B14
	143	16.1	9.81	7.5		B5/B14
	153	15	9.17	5.3		B5/B14
	181	12.6	7.72	6.3		B5/B14
	246	9.3	5.69	7.5		B5/B14
302	7.6	4.63	9.2	B5/B14		
366	6.3	3.82	11.2	B5/B14		
26	88	54	2.3	BON 25	B5/B14	
30	76	46.46	2.6		B5/B14	
34	66	40.6	3		B5/B14	
39	59	35.91	3.4		B5/B14	

0.18



4 Pole (1400 rpm)	26	63	53.33	1.9	BON 20	B5/B14
	31	54	45.89	2.2		B5/B14
	35	47	40.1	2.5		B5/B14
	39	42	35.47	2.9		B5/B14
	49	34	28.5	3.6		B5/B14
	59	28	23.56	4.3		B5/B14
	71	23	19.83	5.1		B5/B14
	78	21	17.86	4.3		B5/B14
	96	17.2	14.62	7		B5/B14
	101	16.3	13.8	5.5		B5/B14
	118	14	11.9	8.6		B5/B14
	143	11.6	9.81	10.4		B5/B14





P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF			
6 Pole (960 rpm)	16.9	136	53.33	0.88	BON 20	B5/B14	
	19.6	117	45.89	1		B5/B14	
	22	102	40.1	1.2		B5/B14	
	25	90	35.47	1.3		B5/B14	
	32	73	28.5	1.7		B5/B14	
	38	60	23.56	2		B5/B14	
	45	51	19.83	2.4		B5/B14	
	50	45	17.86	2		B5/B14	
	62	37	14.62	3.2		B5/B14	
	65	35	13.8	2.6		B5/B14	
	76	30	11.9	4		B5/B14	
	92	25	9.81	4.8		B5/B14	
	98	23	9.17	3.4		B5/B14	
	117	19.7	7.72	4.1		B5/B14	
	158	14.5	5.69	4.8		B5/B14	
	194	11.8	4.63	5.9		B5/B14	
	236	9.7	3.82	7.2		B5/B14	
	16.7	138	54.00	1.5		BON 25	B5/B14
	19.4	118	46.46	1.7			B5/B14
	22	103	40.60	1.9			B5/B14
25	91	35.91	2.2	B5/B14			
31	74	28.88	2.7	B5/B14			


P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF			
6 Pole (960 rpm)	24	141	58.09	2.1	BON 30	B5/B14	
	28	121	50.02	2.5		B5/B14	
	32	106	43.75	2.8		B5/B14	
	36	94	38.73	3.2		B5/B14	
	40	84	34.62	3.6		B5/B14	
	25	134	35.47	0.91		BON 20	B5/B14
	32	107	28.5	1.1			B5/B14
	38	89	23.56	1.4			B5/B14
	45	75	19.83	1.6			B5/B14
	50	67	17.86	1.3			B5/B14
	62	55	14.62	2.2			B5/B14
	65	52	13.8	1.7			B5/B14
	76	45	11.9	2.7			B5/B14
	92	37	9.81	3.2			B5/B14
	98	35	9.17	2.3			B5/B14
	117	29	7.72	2.7		B5/B14	
	16.7	204	54	1		BON 25	B5/B14
	19.4	175	46.46	1.1			B5/B14
	22	153	40.6	1.3			B5/B14
	25	135	35.91	1.5			B5/B14
31	109	28.88	1.8	B5/B14			
38	90	23.85	2.2	B5/B14			
45	76	20.08	2.6	B5/B14			
53	64	17.1	2.2	B5/B14			
68	50	13.21	2.8	B5/B14			
15.5	219	58.09	1.4	BON 30	B5/B14		
18.0	189	50.02	1.6		B5/B14		
21	165	43.75	1.8		B5/B14		
23	146	38.73	2.1		B5/B14		
26	130	34.62	2.3		B5/B14		
32	107	28.3	2.8		B5/B14		
41	82	21.78	3.4		B5/B14		

0.37



P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF			
4 Pole (1400 rpm)	26	129	53.33	0.93	BON 20	B5/B14	
	31	111	45.89	1.1		B5/B14	
	35	97	40.1	1.2		B5/B14	
	39	86	35.47	1.4		B5/B14	
	49	69	28.5	1.7		B5/B14	
	59	57	23.56	2.1		B5/B14	
	71	48	19.83	2.5		B5/B14	
	78	43	17.86	2.1		B5/B14	
	96	35	14.62	3.4		B5/B14	
	101	33	13.8	2.7		B5/B14	
	118	29	11.9	4.2		B5/B14	
	143	24	9.81	5		B5/B14	
	153	22	9.17	3.6		B5/B14	
	181	18.7	7.72	4.3		B5/B14	
	246	13.8	5.69	5.1		B5/B14	
	302	11.2	4.63	6.2		B5/B14	
	366	9.3	3.82	7.6		B5/B14	
	26	131	54	1.5		BON 25	B5/B14
	30	113	46.46	1.8			B5/B14
	34	98	40.6	2			B5/B14
39	87	35.91	2.3	B5/B14			
48	70	28.88	2.9	B5/B14			
59	58	23.85	3.5	B5/B14			
70	49	20.08	4.1	B5/B14			
82	41	17.1	3.4	B5/B14			
95	36	14.81	5.6	B5/B14			



0.55

P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF			
2 Pole (2800 rpm)	53	96	53.33	1.2	BON 20	B5/B14	
	61	83	45.89	1.5		B5/B14	
	70	72	40.1	1.7		B5/B14	
	79	64	35.47	1.9		B5/B14	
	98	51	28.5	2.3		B5/B14	
	119	42	23.56	2.8		B5/B14	
	141	36	19.83	3.4		B5/B14	
	157	32	17.86	2.8		B5/B14	
	203	25	13.8	3.6		B5/B14	
	52	97	54.0	2.1		BON 25	B5/B14
	60	84	46.46	2.4			B5/B14
	69	73	40.60	2.7			B5/B14
	78	65	35.91	3.1			B5/B14
	97	52	28.88	3.8			B5/B14



BON HELICAL GEAR BOXES



P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF		
4 Pole (1400 rpm)	39	128	35.47	0.94	BON 20	B5/B14
	49	103	28.50	1.2		B5/B14
	59	85	23.56	1.4		B5/B14
	71	71	19.83	1.7		B5/B14
	78	64	17.86	1.4		B5/B14
	96	53	14.62	2.3		B5/B14
	101	50	13.80	1.8		B5/B14
	118	43	11.90	2.8		B5/B14
	143	35	9.81	3.4		B5/B14
	153	33	9.17	2.4		B5/B14
	181	28	7.72	2.9	B5/B14	
	246	20	5.69	3.4	B5/B14	
	302	16.7	4.63	4.2	B5/B14	
	366	13.8	3.82	5.1	B5/B14	
	26	194	54	1	BON 25	B5/B14
	30	167	46.46	1.2		B5/B14
	34	146	40.6	1.4		B5/B14
	39	129	35.91	1.5		B5/B14
	48	104	28.88	1.9		B5/B14
	59	86	23.85	2.3		B5/B14
70	72	20.08	2.8	B5/B14		
82	62	17.1	2.3	B5/B14		
95	53	14.81	3.7	B5/B14		
106	48	13.21	2.9	B5/B14		
24	209	58.09	1.4	BON 30	B5/B14	
28	180	50.02	1.7		B5/B14	
32	158	43.75	1.9		B5/B14	
36	139	38.73	2.2		B5/B14	
40	125	34.62	2.4		B5/B14	
49	102	28.3	2.9		B5/B14	
64	78	21.78	3.6	B5/B14		
81	62	17.33	4.5	B5/B14		
24	209	58.09	2.4	BON 35	B5/B14	
28	180	50.02	2.8		B5/B14	
32	158	43.75	3.2		B5/B14	
36	139	38.73	3.6		B5/B14	
40	125	34.62	4.0		B5/B14	
38	132	23.56	0.91		BON 20	B5/B14
45	111	19.83	1.1	B5/B14		
62	82	14.62	1.5	B5/B14		
65	77	13.8	1.2	B5/B14		
76	67	11.9	1.8	B5/B14		
92	55	9.81	2.2	B5/B14		
98	51	9.17	1.6	B5/B14		
117	43	7.72	1.8	B5/B14		
158	32	5.69	2.2	B5/B14		
194	26	4.63	2.7	B5/B14		
236	21	3.82	3.3	B5/B14		



P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF		
22	227	40.6	0.88	BON 25	B5/B14	
25	201	35.91	1		B5/B14	
31	162	28.88	1.2		B5/B14	
38	134	23.85	1.5		B5/B14	
45	113	20.08	1.8		B5/B14	
53	96	17.1	1.5		B5/B14	
61	83	14.81	2.4		B5/B14	
68	74	13.21	1.9		B5/B14	
103	49	8.78	2.4		B5/B14	
15.5	325	58.09	0.92		BON 30	B5/B14
18.0	280	50.02	1.1	B5/B14		
21	245	43.75	1.2	B5/B14		
23	217	38.73	1.4	B5/B14		
26	194	34.62	1.5	B5/B14		
32	159	28.3	1.9	B5/B14		
41	122	21.78	2.3	B5/B14		
52	97	17.33	2.9	B5/B14		
60	84	15.06	3.1	B5/B14		
73	69	12.3	3.8	B5/B14		
15.5	325	58.09	1.5	BON 35	B5/B14	
18.0	280	50.02	1.8		B5/B14	
21	245	43.75	2		B5/B14	
23	217	38.73	2.3		B5/B14	
26	194	34.62	2.6		B5/B14	
32	159	28.3	3.2		B5/B14	
41	122	21.78	3.9		B5/B14	
61	113	45.89	1.1		BON 20	B5/B14
70	98	40.1	1.2	B5/B14		
79	87	35.47	1.4	B5/B14		
98	70	28.5	1.7	B5/B14		
119	58	23.56	2.1	B5/B14		
141	49	19.83	2.5	B5/B14		
157	44	17.86	2.1	B5/B14		
192	36	14.62	3.3	B5/B14		
203	34	13.8	2.7	B5/B14		
52	133	54.00	1.5	BON 25		B5/B14
60	114	46.46	1.8			B5/B14
69	100	40.6	2			B5/B14
78	88	35.91	2.3		B5/B14	
97	71	28.88	2.8		B5/B14	
117	59	23.85	3.4		B5/B14	
139	49	20.08	4.1	B5/B14		
164	42	17.1	3.3	B5/B14		

0.75



2 Pole (2800 rpm)	61	113	45.89	1.1	BON 20	B5/B14	
	70	98	40.1	1.2		B5/B14	
	79	87	35.47	1.4		B5/B14	
	98	70	28.5	1.7		B5/B14	
	119	58	23.56	2.1		B5/B14	
	141	49	19.83	2.5		B5/B14	
	157	44	17.86	2.1		B5/B14	
	192	36	14.62	3.3		B5/B14	
	203	34	13.8	2.7		B5/B14	
	52	133	54.00	1.5		BON 25	B5/B14
	60	114	46.46	1.8			B5/B14
	69	100	40.6	2			B5/B14
78	88	35.91	2.3	B5/B14			
97	71	28.88	2.8	B5/B14			
117	59	23.85	3.4	B5/B14			
139	49	20.08	4.1	B5/B14			
164	42	17.1	3.3	B5/B14			




P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF		
2 Pole (2800 rpm)	48	143	58.09	2.1	BON 30	B5/B14
	56	123	50.02	2.4		B5/B14
	64	107	43.75	2.8		B5/B14
	72	95	38.73	3.2		B5/B14
	81	85	34.62	3.5		B5/B14
4 Pole (1400 rpm)	59	116	23.56	1	BON 20	B5/B14
	71	97	19.83	1.2		B5/B14
	78	88	17.86	1		B5/B14
	96	72	14.62	1.7		B5/B14
	101	68	13.8	1.3		B5/B14
	118	58	11.9	2.1		B5/B14
	143	48	9.81	2.5		B5/B14
	153	45	9.17	1.8	B5/B14	
	181	38	7.72	2.1	B5/B14	
	246	28	5.69	2.5	B5/B14	
	302	23	4.63	3.1	B5/B14	
	366	18.8	3.82	3.7	B5/B14	
	30	228	46.46	0.88	BON 25	B5/B14
	34	199	40.6	1		B5/B14
	39	176	35.91	1.1		B5/B14
	48	142	28.88	1.4		B5/B14
	59	117	23.85	1.7		B5/B14
	70	99	20.08	2		B5/B14
	82	84	17.1	1.7		B5/B14
	95	73	14.81	2.7		B5/B14
	106	65	13.21	2.2		B5/B14
	116	59	12.05	3.4		B5/B14
	141	49	9.93	4.1	B5/B14	
159	43	8.78	2.8	B5/B14		
189	36	7.39	3.3	B5/B14		
257	27	5.45	3.7	B5/B14		
24	285	58.09	1.1	BON 30	B5/B14	
28	246	50.02	1.2		B5/B14	
32	215	43.75	1.4		B5/B14	
36	190	38.73	1.6		B5/B14	
40	170	34.62	1.8		B5/B14	
49	139	28.3	2.2	B5/B14		
64	107	21.78	2.6	B5/B14		
81	85	17.33	3.3	B5/B14		
93	74	15.06	3.5	B5/B14		
24	285	58.09	1.8	BON 35	B5/B14	
28	246	50.02	2		B5/B14	
32	215	43.75	2.3		B5/B14	
36	190	38.73	2.6		B5/B14	
40	170	34.62	2.9		B5/B14	
49	139	28.3	3.6		B5/B14	
64	107	21.78	4.5		B5/B14	













P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF			
6 Pole (960 rpm)	62	112	14.62	1.1	BON 20	B5/B14	
	76	91	11.90	1.3		B5/B14	
	92	75	9.81	1.6		B5/B14	
	98	70	9.71	1.1		B5/B14	
	117	59	7.72	1.4		B5/B14	
	158	43	5.69	1.6		B5/B14	
	194	35	4.63	2.0		B5/B14	
	236	29	3.82	2.4		B5/B14	
	38	182	23.85	1.1		BON 25	B5/B14
	45	153	20.08	1.3			B5/B14
61	113	14.81	1.8	B5/B14			
68	101	13.21	1.4	B5/B14			
75	92	12.05	2.2	B5/B14			
91	76	9.93	2.6	B5/B14			
103	67	8.78	1.8	B5/B14			
122	56	7.39	2.1	B5/B14			
165	42	5.45	2.4	B5/B14			
23	296	38.73	1	BON 30	B5/B14		
26	264	34.62	1.1		B5/B14		
32	216	28.3	1.4		B5/B14		
41	166	21.78	1.7		B5/B14		
52	132	17.33	2.1		B5/B14		
60	115	15.06	2.3		B5/B14		
73	95	12.37	2.8		B5/B14		
88	79	10.28	3.1		B5/B14		
113	61	7.93	3		B5/B14		
143	48	6.31	3.7		B5/B14		
164	42	5.48	3.6	B5/B14			
15.5	444	58.09	1.1	BON 35	B5/B14		
18.0	382	50.02	1.3		B5/B14		
21	334	43.75	1.5		B5/B14		
23	296	38.73	1.7		B5/B14		
26	264	34.62	1.9		B5/B14		
32	216	28.30	2.3		B5/B14		
41	166	21.78	2.9		B5/B14		
52	132	17.33	3.6	B5/B14			

1.1


P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF		
2 Pole (2800 rpm)	98	103	28.5	1.2	BON 20	B5/B14
	119	85	23.56	1.4		B5/B14
	141	71	19.83	1.7		B5/B14
	157	64	17.86	1.4		B5/B14
	192	53	14.62	2.3		B5/B14
	203	50	13.8	1.8		B5/B14
	235	43	11.9	2.8		B5/B14
	285	35	9.81	3.4		B5/B14
	305	33	9.17	2.4		B5/B14
	363	28	7.72	2.9		B5/B14







BON HELICAL GEAR BOXES



P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF			P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF		
2 Pole (2800 rpm)	492	20	5.69	3.4			6 Pole (960 rpm)	32	315	43.75	0.95		
	605	16.7	4.63	4.2				36	279	38.73	1.1		
	733	13.8	3.82	5.1				40	249	34.62	1.2		
	52	194	54	1				49	204	28.3	1.5		
	60	167	46.46	1.2				64	157	21.78	1.8		
	69	146	40.6	1.4				81	125	17.33	2.2		
	78	129	35.91	1.5				93	108	15.06	2.4		
	97	104	28.88	1.9				113	89	12.37	2.9		
	117	86	23.85	2.3				136	74	10.28	3.2		
	139	72	20.08	2.8				177	57	7.93	3.2		
	164	62	17.1	2.3				222	45	6.31	4		
	189	53	14.81	3.7				255	39	5.48	3.8		
	212	48	13.21	2.9				311	32	4.5	4.6		
	48	209	58.09	1.4				374	27	3.74	5.6		
	56	180	50.02	1.7				24	418	58.09	1.2		
	64	158	43.75	1.9				28	360	50.02	1.4		
	72	139	38.73	2.2				32	315	43.75	1.6		
	81	125	34.62	2.4				36	279	38.73	1.8		
	99	102	28.30	2.9				40	249	34.62	2.0		
	129	78	21.78	3.6				49	204	28.30	2.5		
48	209	58.09	2.4	64	157	21.78	3.1						
56	180	50.02	2.8	81	125	17.33	3.8						
64	158	43.75	3.2	93	108	15.06	4.2						
72	139	38.73	3.6	92	110	9.81	1.1						
81	125	34.62	4	117	87	7.72	0.92						
4 Pole (1400 rpm)	96	105	14.62	1.1			6 Pole (960 rpm)	158	64	5.69	1.1		
	118	86	11.9	1.4				194	52	4.63	1.3		
	143	71	9.81	1.7				236	43	3.82	1.6		
	153	66	9.17	1.2				61	166	14.81	1.2		
	181	56	7.72	1.4				75	135	12.05	1.5		
	246	41	5.69	1.7				91	111	9.93	1.8		
	302	33	4.63	2.1				103	98	8.78	1.2		
	366	28	3.82	2.5				122	83	7.39	1.4		
	48	208	28.88	0.96				165	61	5.45	1.6		
	59	172	23.85	1.2				203	50	4.43	2		
	70	145	20.08	1.4				246	41	3.66	2		
	95	107	14.81	1.9				32	317	28.3	0.95		
	106	95	13.21	1.5				41	244	21.78	1.1		
	116	87	12.05	2.3				52	194	17.33	1.4		
	141	72	9.93	2.8				60	169	15.06	1.5		
	159	63	8.78	1.9				73	139	12.37	1.9		
	189	53	7.39	2.3				88	115	10.28	2.1		
	257	39	5.45	2.5				113	89	7.93	2		
	316	32	4.43	3.1				143	71	6.31	2.5		
	383	26	3.66	3				164	61	5.48	2.4		
								200	50	4.5	3		
								241	42	3.74	3.6		








P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF		
6 Pole (960 rpm)	21	490	43.75	1.0	BON 35	B5/B14
	23	434	38.73	1.2		B5/B14
	26	388	34.62	1.3		B5/B14
	32	317	28.30	1.6		B5/B14
	41	244	21.78	2.0		B5/B14
	52	194	17.33	2.5		B5/B14
	60	169	15.06	2.7		B5/B14
	73	139	12.37	3.3		B5/B14
	88	115	10.28	3.8		B5/B14
	113	89	7.93	2.9		B5/B14
	143	71	6.31	3.7		B5/B14
	164	61	5.48	3.7		B5/B14



P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF		
4 Pole (1400 rpm)	48	285	58.09	1.8	BON 35	B5/B14
	56	246	50.02	2		B5/B14
	64	215	43.75	2.3		B5/B14
	72	190	38.73	2.6		B5/B14
	81	170	34.62	2.9		B5/B14
	99	139	28.3	3.6		B5/B14
	118	117	11.9	1	BON 20	B5/B14
	143	96	9.81	1.2		B5/B14
	153	90	9.17	0.89		B5/B14
	181	76	7.72	1.1		B5/B14
	246	56	5.69	1.3		B5/B14
	302	45	4.63	1.5		B5/B14
	366	38	3.82	1.9	B5/B14	
	95	145	14.81	1.4	BON 25	B5/B14
	116	118	12.05	1.7		B5/B14
	141	98	9.93	2.1		B5/B14
	159	86	8.78	1.4		B5/B14
	189	73	7.39	1.7		B5/B14
257	54	5.45	1.9	B5/B14		
316	44	4.43	2.3	B5/B14		
383	36	3.66	2.2	B5/B14		
40	340	34.62	0.88	BON 30	B5/B14	
49	278	28.3	1.1		B5/B14	
64	214	21.78	1.3		B5/B14	
81	170	17.33	1.6		B5/B14	
93	148	15.06	1.8		B5/B14	
113	122	12.37	2.1		B5/B14	
136	101	10.28	2.4	B5/B14		
177	78	7.93	2.3	B5/B14		
222	62	6.31	2.9	B5/B14		
255	54	5.48	2.8	B5/B14		
311	44	4.5	3.4	B5/B14		
374	37	3.74	4.1	B5/B14		
24	571	58.09	0.88	BON 35	B5/B14	
28	491	50.02	1.0		B5/B14	
32	430	43.75	1.2		B5/B14	
36	380	38.73	1.3		B5/B14	
40	340	34.62	1.5		B5/B14	
49	278	28.30	1.8		B5/B14	
64	214	21.78	2.2		B5/B14	
81	170	17.33	2.8		B5/B14	
93	148	15.06	3.1		B5/B14	
113	122	12.37	3.8		B5/B14	
136	101	10.28	4.4		B5/B14	
177	78	7.93	3.3		B5/B14	
222	62	6.31	4.2	B5/B14		
255	54	5.48	4.3	B5/B14		

1.5						
P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF		
2 Pole (2800 rpm)	119	116	23.56	1	BON 20	B5/B14
	141	97	19.83	1.2		B5/B14
	192	72	14.62	1.7		B5/B14
	203	68	13.8	1.3		B5/B14
	235	58	11.9	2.1		B5/B14
	285	48	9.81	2.5		B5/B14
	305	45	9.17	1.8		B5/B14
	363	38	7.72	2.1		B5/B14
	492	28	5.69	2.5		B5/B14
	605	23	4.63	3.1		B5/B14
	733	18.8	3.82	3.7		B5/B14
	69	199	40.6	1		BON 25
	78	176	35.91	1.1	B5/B14	
	97	142	28.88	1.4	B5/B14	
	117	117	23.85	1.7	B5/B14	
	139	99	20.08	2	B5/B14	
	189	73	14.81	2.7	B5/B14	
	212	65	13.21	2.2	B5/B14	
	232	59	12.05	3.4	B5/B14	
	282	49	9.93	4.1	B5/B14	
	319	43	8.78	2.8	B5/B14	
	379	36	7.39	3.3	B5/B14	
	514	27	5.45	3.7	B5/B14	
	48	285	58.09	1.1	BON 30	B5/B14
	56	246	50.02	1.2		B5/B14
	64	215	43.75	1.4		B5/B14
	72	190	38.73	1.6		B5/B14
	81	170	34.62	1.8		B5/B14
	99	139	28.3	2.2		B5/B14
	129	107	21.78	2.6		B5/B14
	162	85	17.33	3.3		B5/B14
	186	74	15.06	3.5		B5/B14



BON HELICAL GEAR BOXES



P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF			
6 Pole (960 rpm)	52	265	17.33	1.1	BON 30	B5/B14	
	60	230	15.06	1.1		B5/B14	
	73	189	12.37	1.4		B5/B14	
	88	157	10.28	1.5		B5/B14	
	113	121	7.93	1.5		B5/B14	
	143	96	6.31	1.9		B5/B14	
	164	84	5.48	1.8		B5/B14	
	200	69	4.5	2.2		B5/B14	
	241	57	3.74	2.6		B5/B14	
	26	529	34.62	0.95	BON 35	B5/B14	
		32	432	28.30		1.2	B5/B14
		41	333	21.78		1.4	B5/B14
		52	265	17.33		1.8	B5/B14
		60	230	15.06		2.0	B5/B14
		73	189	12.37		2.4	B5/B14
		88	157	10.28		2.8	B5/B14
		113	121	7.93		2.1	B5/B14
		143	96	6.31		2.7	B5/B14
164		84	5.48	2.7		B5/B14	
200		69	4.50	3.3		B5/B14	
241		57	3.74	3.5		B5/B14	



P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF				
4 Pole (1400 rpm)	72	279	38.73	1.8	BON 35	B5/B14		
	81	249	34.62	2		B5/B14		
	99	204	28.3	2.5		B5/B14		
	129	157	21.78	3.1		B5/B14		
	162	125	17.33	3.8		B5/B14		
	64	314	21.78	0.89		BON 30	B5/B14	
		81	250	17.33			1.1	B5/B14
		93	217	15.06			1.2	B5/B14
		113	178	12.37			1.5	B5/B14
		136	148	10.28	1.6		B5/B14	
		177	114	7.93	1.6		B5/B14	
		222	91	6.31	2		B5/B14	
		255	79	5.48	1.9		B5/B14	
		311	65	4.5	2.3		B5/B14	
	374	54	3.74	2.8	BON 35	B5/B14		
		40	499	34.62		1.0	B5/B14	
		49	408	28.3		1.2	B5/B14	
		64	314	21.78		1.5	B5/B14	
81		250	17.33	1.9		B5/B14		
93		217	15.06	2.1		B5/B14		
113		178	12.37	2.6		B5/B14		
136		148	10.28	3		B5/B14		
177		114	7.93	2.3		B5/B14		
222		91	6.31	2.9		B5/B14		
255		79	5.48	2.9		B5/B14		
311		65	4.5	3.5		B5/B14		
6 Pole (960 rpm)	374	54	3.74	3.7	B5/B14			
	73	277	12.37	0.94	BON 30	B5/B14		
	88	230	10.28	1		B5/B14		
	113	178	7.93	1		B5/B14		
	143	141	6.31	1.3		B5/B14		
	164	123	5.48	1.2		B5/B14		
	200	101	4.5	1.5		B5/B14		
	241	84	3.74	1.8		B5/B14		
	41	488	21.78	1		BON 35	B5/B14	
		52	388	17.33			1.2	B5/B14
		60	338	15.06	1.4		B5/B14	
		73	277	12.37	1.7		B5/B14	
		88	230	10.28	1.9		B5/B14	
		113	178	7.93	1.5		B5/B14	
		143	141	6.31	1.8		B5/B14	
		164	123	5.48	1.9		B5/B14	
		200	101	4.5	2.3		B5/B14	
	241	84	3.74	2.4	B5/B14			

2.2

2 Pole (2800 rpm)	97	208	28.88	0.96	BON 25	B5/B14	
	117	172	23.85	1.2		B5/B14	
	139	145	20.08	1.4		B5/B14	
	189	107	14.81	1.9		B5/B14	
	212	95	13.21	1.5		B5/B14	
	232	87	12.05	2.3		B5/B14	
	282	72	9.93	2.8		B5/B14	
	319	63	8.78	1.9		B5/B14	
	379	53	7.39	2.3		B5/B14	
	514	39	5.45	2.5	BON 30	B5/B14	
		632	32	4.43		3.1	B5/B14
		765	26	3.66		3	B5/B14
		64	315	43.75		0.95	B5/B14
		72	279	38.73		1.1	B5/B14
		81	249	34.62		1.2	B5/B14
		99	204	28.3		1.5	B5/B14
		129	157	21.78		1.8	B5/B14
		162	125	17.33		2.2	B5/B14
186	108	15.06	2.4	BON 35	B5/B14		
	226	89	12.37		2.9	B5/B14	
	272	74	10.28		3.2	B5/B14	
	353	57	7.93		3.2	B5/B14	
	444	45	6.31		4	B5/B14	
	511	39	5.48		3.8	B5/B14	



P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF		
------------------	------------------	------------------	---	----	---	---

P_{1n} (kW)	n_2 (r/min)	M_{2n} (Nm)	i	SF		
------------------	------------------	------------------	---	----	---	---

3.0

2 Pole (2800 rpm)	99	278	28.3	1.1	BON 30	B5/B14	
	129	214	21.78	1.3		B5/B14	
	162	170	17.33	1.6		B5/B14	
	186	148	15.06	1.8		B5/B14	
	226	122	12.37	2.1		B5/B14	
	272	101	10.28	2.4		B5/B14	
	353	78	7.93	2.3		B5/B14	
	444	62	6.31	2.9		B5/B14	
	511	54	5.48	2.8		B5/B14	
	622	44	4.5	3.4		B5/B14	
	749	37	3.74	4.1		B5/B14	
	81	340	34.62	1.5		BON 35	B5/B14
	99	278	28.3	1.8			B5/B14
	129	214	21.78	2.2			B5/B14
	162	170	17.33	2.8			B5/B14
	186	148	15.06	3.1			B5/B14
226	122	12.37	3.8	B5/B14			
272	101	10.28	4.4	B5/B14			
353	78	7.93	3.3	B5/B14			
444	62	6.31	4.2	B5/B14			
4 Pole (1400 rpm)	93	296	15.06	0.88	BON 30	B5/B14	
	113	243	12.37	1.1		B5/B14	
	136	202	10.28	1.2		B5/B14	
	177	156	7.93	1.2		B5/B14	
	222	124	6.31	1.5		B5/B14	
	255	108	5.48	1.4		B5/B14	
	311	88	4.5	1.7		B5/B14	
	374	73	3.74	2		B5/B14	
	49	556	28.3	0.9	BON 35	B5/B14	
	64	428	21.78	1.1		B5/B14	
	81	340	17.33	1.4		B5/B14	
	93	296	15.06	1.6		B5/B14	
	113	243	12.37	1.9		B5/B14	
	136	202	10.28	2.2		B5/B14	
	177	156	7.93	1.7		B5/B14	
	222	124	6.31	2.1		B5/B14	
255	108	5.48	2.1	B5/B14			
311	88	4.5	2.6	B5/B14			
374	73	3.74	2.7	B5/B14			

4.0

2 Pole (2800 rpm)	162	227	17.33	1.2	BON 30	B5/B14	
	186	197	15.06	1.3		B5/B14	
	226	162	12.37	1.6		B5/B14	
	272	135	10.28	1.8		B5/B14	
	353	104	7.93	1.7		B5/B14	
	444	83	6.31	2.2		B5/B14	
	511	72	5.48	2.1		B5/B14	
	622	59	4.5	2.5		B5/B14	
	749	49	3.74	3.1		B5/B14	
	81	453	34.62	1.1		BON 35	B5/B14
	99	371	28.3	1.3			B5/B14
	129	285	21.78	1.7			B5/B14
	162	227	17.33	2.1			B5/B14
	186	197	15.06	2.3			B5/B14
	226	162	12.37	2.8			B5/B14
	272	135	10.28	3.3			B5/B14
353	104	7.93	2.5	B5/B14			
444	83	6.31	3.1	B5/B14			
511	72	5.48	3.2	B5/B14			
622	59	4.5	3.9	B5/B14			
749	49	3.74	4.1	B5/B14			
4 Pole (1400 rpm)	136	269	10.28	0.89	BON 30	B5/B14	
	177	208	7.93	0.87		B5/B14	
	222	165	6.31	1.1		B5/B14	
	255	144	5.48	1		B5/B14	
	311	118	4.5	1.3		B5/B14	
	374	98	3.74	1.5		B5/B14	
	81	454	17.33	1.1		BON 35	B5/B14
	93	394	15.06	1.2			B5/B14
	113	324	12.37	1.4	B5/B14		
	136	269	10.28	1.6	B5/B14		
	117	208	7.93	1.3	B5/B14		
	222	165	6.31	1.6	B5/B14		
	255	144	5.48	1.6	B5/B14		
	311	118	4.5	2	B5/B14		
	374	98	3.74	2	B5/B14		