



Model	a b	c e	f g	Hollow shaft dimension					Torque arm form		h j	l	M	N Q
				d ₁ d ₂	l ₁ l ₂	l ₃ l ₄	l ₅ s	t ₁ u ₁	k m n	p q				
B-FA..37 B-FA..37/T	158 30	14 31.5	46 15	30h7 45	0.5 123	120 105	17 M10X25	33.3 8	40 12.5 5	20 1	252 172	110	76	112 120
B-FA..47 B-FA..47/T	170 22	14 32	64 12	35h7 50	1 153	150 132	22 M10X25	38.3 10	40 12.5 5	20 1.8	269 189	133	77	128.1 120
B-FA..57 B-FA..57/T	198 31	14 40.5	60 19.5	40h7 55	1 170	166 142	29 M16X40	43.3 12	40 12.5 5	20 2.4	317 210	150	83	136 160
B-FA..67 B-FA..67/T	218 40	14 41	65 21	40h7 55	1 184	180 156	29 M16X40	43.3 12	40 12.5 5	20 3	343 223	161	97	159.5 160
B-FA..77 B-FA..77/T	278 49	22 50	69 28	50h7 70	1 213	210 183	32 M16X45	53.8 14	60 21 10	30 3.2	426 282	193	121	200 200
B-FA..87 B-FA..87/T	348 57	22 62	79 32	60h7 85	1 243	240 210	36 M20X50	64.4 18	60 21 10	30 4.5	531 336	224	152	246.7 250
B-FA..97 B-FA..97/T	395 88	28 70	104 34	70h7 95	1 303	300 270	34 M20X50	74.9 20	80 25 12	40 5.8	623 414	274	178	285 300
B-FA..107 B-FA..107/T	485 108	26 88	100 57	90h7 118	2.5 353	350 313	40 M24X60	95.4 25	80 25 12	40 6	717 456	312	200	332.4 350
B-FA..127 B-FA..127/T	550 138	33 110	125 66	100h7 135	2.5 413	410 373	38 M24X60	106.4 28	100 32 15	60 9	856 530	373	236	362.6 450
B-FA..157 B-FA..157/T	660 170	33 150	140 98	120h7 155	7 503	500 460	36 M24X60	127.4 32	120 32 15	60 9	1021 660	455	286	447 550